SABRELINE 36 SEDAN 2005 MODEL YEAR SPECIFICATION

HULL

Modified "V" hull design with 18 degree deadrise at transom

ISO-NPG gel coat and vinylester back-up resin.

Knitted, bi-axial fiberglass laminates.

Divinycell Cored hull bottom laminate.

Solid frp hull side laminate.

Foam/plywood cored fiberglass stringer system.

Fiberglass swim platform with telescoping SS swim ladder. Hull side rubbing strakes.

PVC rub rail with stainless steel cap.

Imron, split boot stripe.

DECK

Isopthalic gel coat.

Knitted E glass laminate with end grain balsa core.

Molded-in anti-skid deck surfaces.

1-1/4" diameter type 316 stainless steel rail system.

Fiberglass bow pulpit with anchor roller.

Two foredeck lockers with central chain locker.

Recessed side deck walkways.

Starboard side sliding door to main salon.

Stainless steel stair with handrail and teak treads to command bridge.

(3) Hinged cockpit locker hatches with gas strut supports.

Hinged transom door to swim platform.

Flag pole holder and teak flag staff

Lewmar polished aluminum hatches with screens.

Custom stainless steel opening ports with screens.

Custom stainless steel bow chocks.

Custom cast aluminum spring line and stern hawse pipes.

Teak toe rail.

Teak cabin side eyebrow.

FRP cockpit coamings

Cockpit wet bar with teak fiddle

COMMAND BRIDGE

Molded control station console for electronics with storage below.

Settee with 3" cushions and storage lockers below.

Pompanette helm and mate seats, model P2000, 18" pedestals.

Stainless steel perimeter hand rail.

Plexiglass windscreen.

Built-in fiberglass helm footrest in bridge face.

Flybridge access doors (King Starboard) with trash bin behind.

STANDARD ENGINES

Twin Yanmar 6LPA-STP, 6-cylinder, 315-bhp diesels, gray finish, fresh water cooled.

ZF IRM 220 A-1 marine gears.

80-amp, 12-volt alternator on each engine.

1-3/4" Aquamet 22 stainless steel shafts.

PSS drip-less shaft seals.

4-blade NiBrAl propellers to ISO Class S standards.

Groco engine intake strainers.

Sea water cooled exhaust system with in-line mufflers and side exhaust outlets.

Manganese bronze struts with rubber cutlass bearings. Engine room blowers.

White painted engine room. Fully insulated with Soundown foam noise barrier.

FUEL SYSTEM

T shaped Aluminum fuel tank with side deck fill. Racor fuel/water separators with water in fuel alarms. Electric fuel tank level indicator at lower helm station

STEERING AND TRIM SYSTEMS

Teleflex hydraulic steering system lower and upper control stations

Twin bronze rudders with bronze stuffing boxes.

Twin Bennett drop-fin trim tabs (12"x18"x3") with dual actuators.

LOWER CONTROL STATION

Start/stop rocker switches with ignition circuit breaker.

Twin Teleflex shift controls.

Twin Teleflex throttle controls.

Gauges: Beede Tachometer with hour meter, voltmeter, engine oil pressure, transmission oil pressure, engine water temperature.

Engine alarms (light and buzzer) for high water temperature and low oil pressure.

Trim tab controls.

Triple windshield wipers with washers.

4-1/2" compass.

Switch panel with Carlingswitch Contura rocker switches. Includes switches for horn, blower, optional synchronizer, running, anchor and instrument lights, and (3) accessories.

18" Schmitt stainless steel steering wheel.

COMMAND BRIDGE CONTROL STATION

Start/stop rocker switches with ignition circuit breaker.

Twin Teleflex shift controls.

Twin Teleflex throttle controls.

Gauges. Beede Tachometer, voltmeter, engine oil pressure, transmission oil pressure, engine water temperature.

Engine alarms (light and buzzer) for high water temperature and low oil pressure.

Trim tab controls.

4-1/2" Ritchie compass.

Switch panel with Carlingswitch Contura rocker switches.

Includes switches for horn, blower, optional

synchronizer, running, anchor and instrument lights, and (3) accessories.

18" Schmitt stainless steel steering wheel w/tilt.

SAFETY

Four 2-1/2 lb. fire extinguishers.

Bonding system for protection against galvanic corrosion. Propeller shaft brushes

Xintex Fireboy automatic fire extinguishing discharge system with dual override

12-VDC ELECTRICAL SYSTEM

Two group 31, dedicated, AGM, engine start batteries.

Two group 31 AGM ship's batteries.

Battery disconnect and crossover switches in engine room.

Illuminated main circuit breaker distribution panel.

12-volt lighting system with Cantalupi Jeny overhead lights and Danish Cabin reading lights.

Valance accent lighting with dimmer switch.

Flybridge and cockpit courtesy lights.

12-volt DC horn.

Navigation lights: side, steaming, stern and 360 degree anchor light.

Marinco Sealink 12-volt DC outlet on flybridge.

Tinned wire throughout.

120-VAC ELECTRICAL SYSTEM

30-amp, 120-volt AC shore power inlet and 50 ft. cord. Bass illuminated main circuit breaker distribution panel.

120-volt AC outlets in each cabin, engine room and bridge. Galley, head, engine room and bridge receptacles are GFI protected.

Professional Mariner 50-amp/3-bank battery charger.

PLUMBING

Wet bar in cockpit. Includes sink with hot/cold pressure water, fold-down Scandvik faucet.

- (1) Rule 2000 (2000 gph), automatic 12-volt DC bilge pump.
- (1) Rule 1100 (1100 gph), automatic 12-volt DC bilge pump.

Fresh water spigot in engine room.

Two, roto-molded, polyethylene water tanks.

Roto-molded, polyethylene holding tank.

Marelon sea valves on thru-hull fittings below the waterline.

Marelon holding tank discharge seacock.

Macerator pump on holding tank

11 gal. water heater operates on both 120-volt AC and engine heat.

Temperature control valve on hot water system.

12-volt DC hot and cold pressure water w/accumulator tank.

Electric water tank level indicator.

Holding tank full indicator.

DÉCOR

Varnished cherry interior.

Teak and holly cabin soles with two coats of sealer.

Soft headliner panels (except head and shower stall).

Screens on all opening windows, ports and hatches.

Optional fabric and drapery selections.

Dovetailed drawers throughout.

Laminated trims on counters and berth tops

MASTER STATEROOM

Island berth with 6" foam mattress.

Drawers and locker storage under berth.

Direct access to head.

Storage lockers outboard and above berth.

Hanging locker (cedar lined) with louvered door.

Passageway door to main salon.

Full-length, bulkhead mirror.

HEAD

FRP vanity sink with Delta single-lever faucet.

Corian vanity countertop.

Wood trimmed mirror.

Shower stall with curved clear plexiglass door.

Shower seat and wet locker.

Scandvik shower mixer control.

Electric shower sump pump.

Fiberglass sole with anti-skid in head compartment.

Storage lockers.

Teak towel bars

Ventilation blower (12-volt DC).

GALLEY

U-shaped galley down standard.

Galley up version is an available option

High-pressure laminate galley countertop.

Double Scandvik stainless steel sink with single lever Scandvik faucet.

Built-in waste basket.

Drawers and locker storage below counter.

Lockers outboard and above counter with louvered doors.

Seaward, Gourmet 2-burner electric cook top (#G2247D).

Panasonic convection microwave.

Norcold, under counter, AC/DC refrigerator/freezer.

Powered (12-volt DC) galley ventilation.

MAIN SALON

Counter/chart table with bottle storage under.

"L" settee with Hi-Lo table. Removeable leaf.

Settee converts to double berth with filler cushion.

Tool drawer and locker storage under settee.

Lower helm station forward with swing up helm seat

Bomon, painted, aluminum-framed windows with interior wood trim. Sliding, screened windows port and starboard.

Sliding access door to starboard side deck.

Sound deadening headliner panels.

Cantalupi halogen lights in overhead

Danish Cabin reading lights

Mini-blinds on after side and back windows. (Mini-blinds not provided on aft door, sliding door or forward side windows.)

Aluminum 2000 hinged access door to aft cockpit. Includes top-drop window with screen.

Subject to change without notice 7/04